RICOH imagine, change. A3 B/W MFP **MP 2553SP** MP 3053SP **MP 3053AD** MP 3353SP MP 3353AD W- 20 MP 3053SP MP 2553SP 25 B/W 30 B/W MP 3053AD MP 3353SP MP 3353AD 30 B/W 33 B/W 33 B/W

Eco-friendly and compact B/W MFPs

Increasing your office productivity while simultaneously reducing your environmental impact may appear to be a paradox, but the MP 2553SP/MP 3053SP/MP 3053AD/MP 3353SP/MP 3353AD enable you to meet both objectives. These A3 black-and-white multifunction printers incorporate Ricoh's latest controller to give you features to transform your productivity. These include Searchable PDF, ID Card Copy, and extensive scan/fax capabilities. At the same time, a short warm-up time, low power consumption and standard duplex make these compact MFPs environmentally responsible.

- · Advanced controller powers value-added functionalities
- Energy-saving features reduce operating costs
- · Compact, with built-in finisher
- · Fast, efficient and productive
- · Easy to operate and maintain



Multi-function; multi-benefit

Improved productivity

Ricoh's advanced GWNX controller powers features that improve productivity. Save time searching for documents with Searchable PDF. Scan in colour and send to email, folder, USB, SMB, FTP, URL and NCP. To fax, choose from Internet Fax (T.37), IP-Fax, LAN-Fax, PC-Fax, G3-Fax or remote faxing. Network connectivity is built-in as standard, and @Remote gives you internet-based support for remote management.

Green, from start to finish

The Ricoh line-up has been designed with the environment in mind. Paper-saving features include print preview, quota setting, paperless fax and standard duplex. The Eco Friendly Indicator displays usage status in a pop-up screen. TEC values are extremely low, reducing power consumption and CO2 emissions. In addition, these devices comply with the latest Energy Star and BAM directives.



Speedy, yet compact

The MP 2553SP/MP 3053SP/MP 3053AD/MP 3353SP/MP 3353AD are up and running in virtually no time at all, thanks to a warm-up time of only 15.5 seconds, and a first copy/print speed of 4.5 seconds. Yet, they are surprisingly compact for such high-spec A3 MFPs. One reason is the built-in finisher which avoids the necessity for an external finisher.

Remarkably easy to use

Operating these MFPs is a delight. The large, tiltable LCD screen displays clear, animated menus with buttons that are easy to read and use. The screen can be customised for each user with selectable icons, and the keyboard is available in QWERTY or AZERTY. Routine troubleshooting and maintenance tasks are performed simply via full front access. They print from USB memory stick or SD card, while the HDD has a high memory capacity which saves you time during printing.



MP 2553SP/MP 3053SP/MP 3053AD/MP 3353SP/MP 3353AD

MAIN SPECIFICATIONS

GENERAL

Warm-up time: 15 seconds 4.2 seconds First output speed

Continuous output speed: 25/30/30/33/33 pages per minute Standard: 1,536/1,536/512/1,536/512 Memory:

MB

HDD: 250 GB (Option) Dimensions (W x D x H): 587 x 675 x 710 mm

Weight: 75 ka

Power source: 220 - 240 V, 50/60 Hz

COPIER

Laser beam scanning and electro-Copying process:

photographic printing

Scanning element: One-dimensional solid scanning

through CCD Up to 999 copies Multiple copying: Resolution: 600 dpi

From 25% to 400% in 1% steps

PRINTER (MP 3053SP, MP 3353SP) (Option)

Printer language: Standard: PCL5e, PCL6, XPS, PDF

direct print

Option: Adobe® PostScript® 3™

Print resolution: 600 x 600 dpi

Standard: USB 2.0, SD slot, Ethernet 10 Interface:

base-T/100 base-TX. Ethernet 1000

Base-T

Option: Bi-directional IEEE 1284 Wireless LAN (IEEE 802.11a/b/g/n),

Bluetooth

TCP/IP (IP v4, IP v6), IPX/SPX (Option) Network protocol: Windows® XP Windows® Vista Windows® environments:

> Windows® 7, Windows® 8, Windows® Server 2003, Windows® Server 2003R2, Windows® Server 2008, Windows® Server 2008R2, Windows®

Server 2012

Mac OS environments: Macintosh OS X v10.5 or later UNIX Sun® Solaris, HP-UX, SCO UNIX environments:

OpenServer, RedHat® Linux, IBM®

AIX

Novell® Netware® environments: v6.5 (Option) SAP® R/3® environments: SAP® R/3®

Other supported environments: NDPS Gateway, AS/400® using OS/

400 Host Print Transform, IBM iSeries

SCANNER

Scanning speed: Full colour: Maximum 80 originals per

Maximum 80 originals per minute

300 dpi: B/W Maximum: 600 dpi

A3, A4, A5, B4, B5 Original size: Bundled drivers: Network TWAIN

E-mail, Folder, SMB, FTP, URL, NCP

FAX (Option)

PSTN PRX Circuit: Compatibility: ITU-T (CCITT) G3

Resolution: 8 x 3.85 line/mm, 200 x 100 dpi 8 x 7.7 line/mm, 200 x 200 dpi

Transmission speed: G3: 2 second(s) (200 x 100 dpi, JBIG)

Modem speed: Maximum: 33.6 Kbps 1 second(s) Scanning speed: Standard: 4 MB Memory capacity: Maximum: 28 MB

PAPER HANDLING

Standard paper tray(s): A3, A4, A5, A6, Recommended paper size: B4, B5, B6

Bypass tray: A3, A4, A5, A6, B4, B5, B6 Maximum: 3,150 sheets

Paper input capacity: Maximum: 1.600 sheets Paper output capacity:

Paper weight: Standard paper tray(s): 52 - 157 g/m²

Bypass tray: 52 - 157 g/m²

ECOLOGY

Power consumption: Maximum: 1.600 W

Ready mode: 152/152//152 W Sleep mode: 0.61/0.61//0.61 W TEC (Typical Electricity Consumption):

1,303/1,674//1.826 W/h

SOFTWARE

Standard: SmartDeviceMonitor, Web

SmartDeviceMonitor®. Web Image

Monitor

Optional GlobalScan NX, Card Authentication Package, Unicode Font Package for

SAP. Remote Communication Gate S

OPTIONS

ADF handle, 1 x 550-sheet paper tray, 2 x 550-sheet paper tray, 2,000-sheet large capacity tray, Bridge unit, 1,000-sheet finisher, Internal finisher, 1,000sheet booklet finisher, Punch kit for booklet finisher, Punch kit for internal finisher, Internal shift tray, One-bin tray, Caster table, Low cabinet, Printer/ Scanner option, Printer unit, Scanner enhance option, Hard Disk Drive, Bidirectional IEEE 1284. Wireless LAN (IEEE 802.11a/b/g/n), Bluetooth, Netware, PostScript3, Browser unit, File format converter, Key counter bracket, Card reader bracket, Copy Data Security Unit, Fax Connection Unit, 2nd Super G3 port, Fax memory, Fax option, Unicode Font Package for SAP, OCR Unit, Smart Card Reader Built-in Unit, Finisher adapter

CONSUMABLES

Black: 11,000 prints Toner capacity:

ISO9001 certified, ISO14001 certified, ISO27001 certified

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure. The images in this brochure are not real photographs and slight differences in detail might appear.

Copyright © 2013 Ricoh Europe PLC. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/ or incorporated into other works without the prior written permission of Ricoh Europe PLC.



www.ricoh-europe.com